

[xYou](#) [Writ](#) [Images](#) [Videos](#) [Maps](#) [News](#) [Shopping](#) [Gmail](#) [More](#)

Sign in

My Subjects

Google scholar

determine the address of PID and idle

Search

Advanced Scholar Search

Scholar Articles and patents

anytime

include citations

Create email alert

Results 1 - 10 of about 6,040 (0.05 sec)

**Virtualizing serial bus information point by address mapping via a parallel port**

DG Edin - US Patent 6 119,196, 2000 - Google Patents  
 ... 430 420 TRANSMITTER PROCESSOR REGISTER #10 - 4 4A r CRC GENERATOR DATA MUX  
 CONSTANT #16 230 --USB TRANSMITTER PID ADDR ENDP ... 3 512 510 /EPI COMPARE  
 CIRCUIT ADDR EPI FIFO K X 8 OUT WE IN 514 - 4 EPI ADDRESS GENERATOR IF IN ...  
[Cited by 11](#) - [Related articles](#) - [All 2 versions](#)

**System and method for reducing power consumption in a universal serial bus device**

Ds Wright, Tj Whisnau - US Patent 6 616,978, 2004 - Google Patents  
 ... US Patent Nov. 9 2004 Sheet 4 of 5 US 6 616,978 B2 SYNC PID ADDRESS CRC SYNC PID  
 DATA CRC SYNC PID FIG. ... 15. The apparatus according to claim 14, wherein said device is further  
 configured to **determine an address** of said particular type of packet. 60 16. ...  
[Cited by 13](#) - [Related articles](#) - [All 2 versions](#)

**Idle period signalling in a packet switching system**

ML Larson, AK Radachuk - US Patent 6 646,287, 1987 - Google Patents  
 ... The detector identifies **idle** packets by their **PID** field and discards them--blocks them from ... TRUNK  
 CONTROLLER MEMORY ADDRESS BUS 1417 1418 FROM/TO SWITCH NETWORK 116  
 SWITCH ... For example, a re-ceiving node cannot **determine** from receipt of **idle** code ...  
[Cited by 6](#) - [Related articles](#) - [All 2 versions](#)

**Personal mobility and communication termination for users operating in a plurality of heterogeneous networks**

PID Lee, KS Biesu, SH Zhou, W Yuan, ... - US Patent ... 2000 - Google Patents  
 ... Particularly, if an immediate conversation is required, it is difficult to **determine** a par- ticular  
 number to dial or **address** to employ to immediately reach the user. ... However, if Tom Jones does  
 not have an email **address**, his PID could be his phone number, (972) 684-0800. ...  
[Cited by 16](#) - [Related articles](#) - [All 2 versions](#)

**Communication control apparatus for common bus connection devices**

M Mohrmann - US Patent 7 779,190, 2010 - Google Patents  
 ... bus to the com- mon bus, and an access suspend unit configured to **determine** that another ... in  
 the device in question when the input determination unit determines that the **address** of the ... 2bit  
 EOP CPO16 DATA PID SYNC 16 HANDSHAKE PACKET Sbit Sbit SYNC PID 2bit EOP ...  
[Related articles](#) - [All 4 versions](#)

**Method and apparatus for a Gigabit Ethernet MAC (GMAC)**

V Huntley - US Patent 6 969,557, 2007 - Google Patents  
 ... processing may include performing Layer 2, eg. Media Access Control (MAC) layer, or Layer  
 3, eg. Net- work layer, **address** look-up to **determine** the forwarding control information such as,  
 the **destination address** (eg. a multicast **address** or egress **PID** and egress ...  
[Cited by 33](#) - [Related articles](#) - [All 2 versions](#)

**Early availability of forwarding control information**

M Mohrmann - US Patent 6 320,858, 2001 - Google Patents  
 ... Access Control (MAC) layer, or Layer 3, eg. Net- 10 work layer, **address** look-up to **determine**  
 the forwarding ... or not the cell is to be forwarded from the output queue to a single **PID** (eg. in ... When  
 the cell is part of a unicast packet, the **destination address** may be represented by a ...  
[Cited by 46](#) - [Related articles](#) - [All 2 versions](#)

**System, apparatus and method for performing look-ahead lookup on predictive information in a cache memory**

ZS Haskura, R Choudak, BW Simenau - US Patent ... 2007 - Google Patents  
 ... **Arbiter** 118 is configured to **determine** which prediction of the generated predictions is to ... ciated  
 therewith can include a prediction identifier ("PID") 20 and a corresponding target **address**. A  
**PID** (not shown) identifies the trigger **address** (or a representation thereof) that caused ...  
[Related articles](#) - [All 4 versions](#)

**Address routing using address-sensitive mask decimation scheme**

VA Huntley - US Patent 6 229,172, 2001 - Google Patents  
 ... search. A mask is applied to an **address**, such as a destination Internet Protocol (IP)  
**address**, to **determine** a masked **address** that is to be used for purposes of locating  
 a matching entry in the forwarding database. The forwarding ...  
[Cited by 13](#) - [Related articles](#) - [All 2 versions](#)

**Effects of wi-fi and bluetooth battery exhaustion attacks on mobile devices**

et al Moyers, JP Espinosa, ... - (HICSS) 2010 43rd ... 2010 - IEEE explore.com/eng  
 ... The **PID** chosen for all attack testing purposes was based on random selection prior to device ...  
 in Table 5. - Ping Flood: Ping is a troubleshooting network tool used to **determine** if a ... was launched  
 at POA 1 using Backtrack 3 and the command: hping3 -faster -cPOA1 IP **Address**. ...  
[Cited by 3](#) - [Related articles](#) - [All 2 versions](#)

[Create email alert](#)

Result Page: 1 2 3 4 5 6 7 8 9 10 **Next**

determine the address of PID and idle

[About Google Scholar](#) - [About Google](#) - [My Citations](#)

©2011 Google